



DIN Rail Power Supply

Highlight:

- A. CE approved
- B. AC85-AC264V input
- C. Overload & Over voltage protection

General Specification:

Model	RPS-15-12	RPS-15-24
Output	DC voltage	12V
	Rated current	1.25A
	Current range	0 ~ 1.25A
	Rated power	15W
	Ripple noise	120mVp-p
	Voltage ADJ. range	10.28--13.2V
	Voltage tolerance	±1.0%
	Line regulation	±1.0%
	Load regulation	±1.0%
	Setup, rise time	1000ms, 50ms/230VAC 200ms, 30ms/115VAC at full load
Input	Hold time(Typ.)	70ms/230VAC 16ms/115VAC at full load
	Voltage range	85 ~ 264VAC 120 ~ 370VDC
	Frequency range	47 ~ 63Hz
	Efficiency(Typ.)	84% 85%
	AC current	0.88A/115VAC 0.48A/230VAC
Protection	Inrush current(max.)	COLD START 35A/115VAC 65A/230VAC
	Overload	105-160% rated output power Protection type: Constant current limiting, recovers automatically after fault condition is removed
	Over voltage	13.8 ~ 16.2V 27.6 ~ 32.4V Protection type: Shut down o/p voltage, re-power on to recover
Environment	Working temp.	-20 ~ +60°C
	Working humidity	20 ~ 90% RH non-condensing
	Storage Temp. humidity	-40 ~ +85°C, 10 ~ 95% RH
	Temp. coefficient	±0.03%/°C (0 ~ 50°C)
	Vibration	10 ~ 500Hz, 2G 10min./1cycle, 60min. each along X, Y, Z axes
Safety&EMC	Safety standards	Design refer to TUV EN60950-1, EN50178
	Withstand voltage	I/P-O/P: 3KVAC I/P-FG: 1.5KVAC O/P-FG: 0.5KVAC
	Isolation resistance	I/P-O/P, I/P-FG, O/P-FG: 100M Ohms/500VDC
	EMI conduction&radiation	Compliance to EN55022 (CISPR22) Class B

Others	Harmonic current	Compliance to EN61000-3-2,-3
	EMS immunity	Compliance to EN61000-4-2, 3, 4, 5; ENV50204, EN55024, Light industry level, criteria A
	MTBF	1172.3K hrs min. MIL-HDBK-217F (25°C)
	Dimension	25×93×56mm(W x H x D)
	Packing	0.1Kg; 140pcs/15KG/0.92CUFT

Dimensions: 25×93×56mm(W x H x D)

